

PRODUCTS CATALOGUE

"AT EASE IN YOUR CONSTRUCTION SITE"





Ritmo meets all your welding needs in your jobsite



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.



DVANTAGE RITMO



RITMO WORLDWIDE

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

TRAINING

From many years now, we have decided that the best way to grant a client/ distributor a perfect knowledge of our products is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the "first aid" when necessary.

PRESALES TECHNICAL ASSISTANCE

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

GLOBAL ADVICE

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

AFTER SALES TECHNICAL ASSISTANCE

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.

STARTING AND TESTING

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.

RITMO'S BUTT FUSION MACHINES: WORK PHILOSOPHY AVAILABLE TO EVERYONE!

- MANUAL

welding machines without hydraulic gearcase



- HYDRAULIC

welding machines with hydraulic gearcase



- EASY LIFE SYSTEM HIGH LEVEL PERFORMANCE

automated welding cycle
welding machines with special hydraulic gearcase
Hardware and Software interact to the entire workflow
repetition of welding cycles
GPS, data-logging and report PDF,
APP "SET & GO PRO" (optional)



- ALL TERRAIN HIGH LEVEL PERFORMANCE

self-contained generator on board
self-propelled
trolley with wheels
welding machines with special hydraulic gearcase
automated welding cycle
Hardware and Software interact to the entire workflow
repetition of welding cycles
GPS, data-logging and report PDF,
APP "SET & GO PRO" (optional)




- CNC HIGH LEVEL PERFORMANCE

automatic welding cycle special hydraulic gearcase and machine body with integrated mechanical extraction of heating plate Hardware and Software interact to the entire workflow repetition of welding cycles GPS, data-logging and report PDF






ALL TERRAIN LINE - TRAILER LINE HIGH LEVEL PERFORMANCE



DIFFERENCES BETWEEN ALL TERRAIN LINE AND TRAILER LINE















watch the video

DELTA 630 ALL TERRAIN

DELTA 630 ALL TERRAIN is powered by a low-vibration diesel engine, suitable for welding thermoplastic pipes for the transport of water, gas and other fluids under pressure, up to \emptyset 630 mm (24" IPS"). Machine can fuse pipes according to the ISO 21307 High Pressure standard.

Standard machine features:

- Working range: Ø 225* 630 mm (8" IPS 24" DIPS); *Ø 225 mm from SDR 26 to SDR 7
- 4 steering wheels drive
- Diesel-engine 2200 cc 22,7 Kw
- Self-contained with on-board generator
- Sliding 3rd CLAMP for fittings welding
- Automatic welding System "Easy Life". **Easy Life system is "Wi-Fi" ready and works together with the App "SET & GO PRO".** possibility to pre-set 20 customized welding cycles
- DATA-LOGGING with GPS; memory 4000 report
- Detachable Control Panel
- Remotely wire-controlled up to 12 m
- Trench-Friendly
- SmartLock Inserts
- Hydraulic Lifts
- Hydraulic-controlled Clamps and Milling cutter
- Climbs rough terrain up to 30%

STANDARD COMPOSITION



Machine body



Hydraulic Rollers



Hydraulic clamps



Control panel with GPS



Hydraulic Milling cutter



Hydraulic Heating plate

TECHNICAL FEATURES



225 ÷ 630 mm 4 STEERING WHEELS DRIVE

SELF CONTAINED WITH ON-BOARD GENERATOR

| V | Vorking range | 225* ÷ 630 mm; 8" IPS ÷ 24" DIPS |
|---|-------------------------------------|---|
| N | /laterials | HDPE, PP For other materials contact RITMO S.P.A. |
| Е | ngine | 2200 cc - 22,7 Kw |
| F | uel type | Diesel |
| F | uel tank capacity | 40 Litres |
| C | Operational tank capacity | 12 Hours |
| Н | lydraulics reservoir capacity | 80 Litres |
| D | Dimensions machine body (W x D x H) | 2200 x 3100 x 2000 mm 86.6" x 122" x 78.8" |
| V | Veight machine body | 800 Kg (1764 lb) |
| V | Veight standard composition | 3000 Kg (6614 lb) |

*225 mm from SDR 26 to SDR 7

ON REQUEST







Inserts Tool for flange necks

App "Set & Go Pro"



Inserts Ø 8"÷ 24" IPS; 8"÷ 20" DIPS; KIT for IN-DITCH USE, HS Roller 630, KIT hoist, metal cage for transport



U.S.A.











BUTT FUSION MACHINES REFERENCE



| WORKING RANGE Ø mm | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 | 1200 | 1400 | 1600 |
|---------------------------|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|
| GAMMA 160 | | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | | | | | | | | | | | | | | | | | | | |
| DELTA 160 M | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | | | | | | | | | | | | | | | | | | | |
| DELTA 200 M | | | | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | | | | | | | | | | | | | | | | | |
| BASIC 160 | | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | | | | | | | | | | | | | | | | | | | |
| BASIC 200 | | | | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | | | | | | | | | | | | | | | | | |
| BASIC 250 | | | | | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | | | | | | | | | | | | | | | |
| BASIC 315 | | | | | | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | | | | | | | | | | | | | |
| BASIC 355 | | | | | | | | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | | | | | | | | | | | | |
| COMPACT 355 | | | | | | | | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | | | | | | | | | | | | |
| BASIC 160 EASY LIFE | | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | | | | | | | | | | | | | | | | | | | |
| BASIC 200 EASY LIFE | | | | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | | | | | | | | | | | | | | | | | |
| BASIC 250 EASY LIFE | | | | | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | | | | | | | | | | | | | | | |
| BASIC 315 EASY LIFE | | | | | | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | | | | | | | | | | | | | |
| BASIC 355 EASY LIFE | | | | | | | | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | | | | | | | | | | | | |
| DELTA 500 EASY LIFE | | | | | | | | | | | | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | | | | | | | | | |
| DELTA 630 EASY LIFE | | | | | | | | | | | | | | | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | | | | | | | |
| DELTA 500 | | | | | | | | | | | | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | | | | | | | | | |
| DELTA 630 | | | | | | | | | | | | | | | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | | | | | | | |
| DELTA 800 | | | | | | | | | | | | | | | | | | | | 500 | 560 | 630 | 710 | 800 | | | | | |
| DELTA 1000 | | | | | | | | | | | | | | | | | | | | | | 630 | 710 | 800 | 900 | 1000 | | | |
| DELTA 1200 | | | | | | | | | | | | | | | | | | | | | | | 710 | 800 | 900 | 1000 | 1200 | | |
| DELTA 1600 ECO / 1600 HDR | | | | | | | | | | | | | | | | | | | | | | | | 800 | 900 | 1000 | 1200 | 1400 | 1600 |
| DELTA 250 TRAILER | | | | | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | | | | | | | | | | | | | | | |
| DELTA 355 TRAILER | | | | | | | | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | | | | | | | | | | | | |
| DELTA 355 ALL TERRAIN | | | | | | | | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | | | | | | | | | | | | |
| DELTA 500 TRAILER | | | | | | | | | | | | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | | | | | | | | | |
| DELTA 500 ALL TERRAIN | | | | | | | | | | | | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | | | | | | | | | |
| DELTA 630 TRAILER | | | | | | | | | | | | | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | | | | | | | |
| DELTA 630 ALL TERRAIN | | | | | | | | | | | | | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | | | | | | | |
| DELTA 1000 TRAILER | | | | | | | | | | | | | | | | 315 | 355 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 | | | |
| DELTA DRAGON 250 CNC | | | | | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | | | | | | | | | | | | | | | |
| DELTA DRAGON 315 CNC | | | | | | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | | | | | | | | | | | | | |
| WORKING RANGE Ø mm | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 | 1200 | 1400 | 1600 |

| стѕ | 1" | 1%" | 1½" | 2" | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------------|----|-----|-----|----|----|-------|-------|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--------|
| IPS | | | | | 1" | 11/4" | 11/2" | 2" | 3" | 4" | 5" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 22" | 24" | 26" | 28" | 30" | 32" | 34" | 36" | 42" | 48" | 52" | 54" | 63" |
| GAMMA 160 | | | | | • | • | • | • | | ٠ | • | | | | | | | | | | | | | | | | | | | | | \Box |
| DELTA 160 M | • | • | | ٠ | • | • | • | ٠ | ٠ | ٠ | • | | | | | | | | | | | | | | | | | | | | | |
| DELTA 200 M | | | | | | | | • | • | • | • | ٠ | | | | | | | | | | | | | | | | | | | | |
| BASIC 160 | | | | | • | • | • | • | • | ٠ | • | | | | | | | | | | | | | | | | | | | | | |
| BASIC 200 | | | | | | | | • | • | • | • | • | | | | | | | | | | | | | | | | | | | | |
| BASIC 250 | | | | | | | | • | • | ٠ | • | • | • | | | | | | | | | | | | | | | | | | | |
| BASIC 315 | | | | | | | | | • | • | • | • | • | • | | | | | | | | | | | | | | | | | | |
| BASIC 355 | | | | | | | | | | • | • | • | • | • | • | • | | | | | | | | | | | | | | | | |
| COMPACT 355 | | | | | | | | | | ٠ | • | ٠ | • | ٠ | • | ٠ | | | | | | | | | | | | | | | | |
| BASIC 160 EASY LIFE | | | | | • | • | • | • | • | ٠ | • | | | | | | | | | | | | | | | | | | | | | |
| BASIC 200 EASY LIFE | | | | | | | | • | • | • | • | • | | | | | | | | | | | | | | | | | | | | |
| BASIC 250 EASY LIFE | | | | | | | | • | • | • | • | • | • | | | | | | | | | | | | | | | | | | | |
| BASIC 315 EASY LIFE | | | | | | | | | • | ٠ | • | • | • | ٠ | | | | | | | | | | | | | | | | | | |
| BASIC 355 EASY LIFE | | | | | | | | | | • | • | ٠ | • | ٠ | ٠ | ٠ | | | | | | | | | | | | | | | | |
| DELTA 500 EASY LIFE | | | | | | | | | | | | | • | • | • | • | • | • | | | | | | | | | | | | | | |
| DELTA 630 EASY LIFE | | | | | | | | | | | | | | ٠ | • | • | • | • | • | • | • | | | | | | | | | | | |
| DELTA 500 | | | | | | | | | | | | | • | ٠ | ٠ | • | • | • | | | | | | | | | | | | | | |
| DELTA 630 | | | | | | | | | | | | | | ٠ | • | • | • | • | • | • | • | | | | | | | | | | | |
| DELTA 800 | | | | | | | | | | | | | | | | | | | • | • | • | • | • | • | | | | | | | | |
| DELTA 1000 | | | | | | | | | | | | | | | | | | | | | • | • | • | • | • | • | • | | | | | |
| DELTA 48" | | | | | | | | | | | | | | | | | | | | | | | • | • | • | • | • | • | • | | | |
| DELTA 1600 ECO / 1600 HDR | | | | | | | | | | | | | | | | | | | | | | | | | • | • | • | • | • | • | • | • |
| DELTA TRAILER 250 | | | | | | | | • | • | • | • | • | • | | | | | | | | | | | | | | | | | | | |
| DELTA 355 TRAILER | | | | | | | | | | • | • | • | • | ٠ | • | • | | | | | | | | | | | | | | | | |
| DELTA 355 ALL TERRAIN | | | | | | | | | | • | • | • | • | • | • | • | | | | | | | | | | | | | | | | |
| DELTA 500 TRAILER | | | | | | | | | | | | • | • | ٠ | • | • | • | • | • | | | | | | | | | | | | | |
| DELTA 500 ALL TERRAIN | | | | | | | | | | | | • | • | • | • | • | • | • | • | | | | | | | | | | | | | |
| DELTA 630 TRAILER | | | | | | | | | | | | | • | • | • | • | • | • | • | • | • | | | | | | | | | | | |
| DELTA 630 ALL TERRAIN | | | | | | | | | | | | | • | • | • | • | • | • | • | • | • | | | | | | | | | | | |
| DELTA 1000 TRAILER | | | | | | | | | | | | | | | | • | • | • | • | • | • | • | • | • | • | • | • | | | | | |
| IPS | | | | | 1" | 11/4" | 11/2" | 2" | 3" | 4" | 5" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 22" | 24" | 26" | 28" | 30" | 32" | 34" | 36" | 42" | 48" | 52" | 54" | 63" |

| DIPS | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" | 30" | 36" | 42" | 48" | 54" | 60" |
|---------------------------|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| GAMMA 160 | | • | | | | | | | | | | | | | | | |
| DELTA 160 M | • | • | | | | | | | | | | | | | | | |
| DELTA 200 M | • | • | ٠ | | | | | | | | | | | | | | |
| BASIC 160 | • | ٠ | | | | | | | | | | | | | | | |
| BASIC 200 | • | • | • | | | | | | | | | | | | | | |
| BASIC 250 | • | • | • | • | | | | | | | | | | | | | |
| BASIC 315 | • | • | • | • | • | | | | | | | | | | | | |
| BASIC 355 | • | ٠ | • | • | • | • | | | | | | | | | | | |
| COMPACT 355 | • | • | • | • | • | ٠ | | | | | | | | | | | |
| BASIC 160 EASY LIFE | • | • | | | | | | | | | | | | | | | |
| BASIC 200 EASY LIFE | • | • | • | | | | | | | | | | | | | | |
| BASIC 250 EASY LIFE | • | • | • | • | | | | | | | | | | | | | |
| BASIC 315 EASY LIFE | • | • | • | • | • | | | | | | | | | | | | |
| BASIC 355 EASY LIFE | • | • | • | • | • | • | | | | | | | | | | | |
| DELTA 500 EASY LIFE | | | | • | • | ٠ | • | • | • | | | | | | | | |
| DELTA 630 EASY LIFE | | | | | • | ٠ | • | • | • | ٠ | | | | | | | |
| DELTA 500 | | | | • | • | | • | • | • | | | | | | | | |
| DELTA 630 | | | | | • | • | • | • | • | ٠ | | | | | | | |
| DELTA 800 | | | | | | | | | • | ٠ | • | | | | | | |
| DELTA 48" | | | | | | | | | | | | • | • | • | | | |
| DELTA 1600 ECO / 1600 HDR | | | | | | | | | | | | • | | | | | • |
| DELTA TRAILER 250 | • | • | • | • | | | | | | | | | | | | | |
| DELTA 355 TRAILER | | • | • | • | • | • | • | | | | | | | | | | |
| DELTA 355 ALL TERRAIN | | • | • | • | • | • | • | | | | | | | | | | |
| DELTA 500 TRAILER | | | • | • | • | • | • | ٠ | ٠ | | | | | | | | |
| DELTA 500 ALL TERRAIN | | | • | • | • | • | • | • | • | | | | | | | | |
| DELTA 630 TRAILER | | | | • | • | • | • | • | • | • | • | | | | | | |
| DELTA 630 ALL TERRAIN | | | | • | • | • | • | • | • | • | • | | | | | | |
| DELTA 1000 TRAILER | | | | | | | • | • | • | • | • | • | • | | | | |
| DIPS | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" | 30" | 36" | 42" | 48" | 54" | 60' |




















RITMO S.p.A. Via A. Volta, 35/37 - 35037 Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888 Fax +39 049 9901993

> info@ritmo.it www.ritmo.it

